			Г	Т	Т	Т	T	Т	T	Т	Т	7	Г	Г	Т	T	Т	7		Г	Г	T	T	Т	Т	\neg			Г	Т	Т	T	Т	Т	Т	Т	_	Г	T	Т	_	Г	Т	Т	7			Т	Т	7	Г
		\Box	L,	T	T	I		1	1		1				I	1					-	I	I	1	1	J		L			-	I	1	1	#	3	10	08	8	0	I	L	1	1		C	\sqsubset'		#	J	İ
H	H	H	+	+	+	+	+	+	+	+	+	1	-	+	+	+	+	+	Н	-	H	1	+	-	7			H	M	-	-	-	1	+	+	4	n		A	H	5/	7	h	2	4	-	-	+	+	1	-
	口	Ľ	Ľ	上	上	İ		T	1	士	士	J			İ	1				İ	-		7	T	7					1		1	1	1		7	-		T	1		Ľ	T	1	_			上			
		1	1										L				1		1							1	(1					1				1					1					('			J	Ĺ

1080 DEADLOCK

1080-1: KEYED ONE SIDE 1080-2: KEYED BOTH SIDES **LOCK SIZE:** 5½" × 1½" × 3¾" **LOCK WEIGHT: 7 POUNDS** BOLT SIZE: 2" × 3/4" BOLT THROW: 3/4"

APPLICATION: Swinging cell doors, corridor doors, storage room doors. High security doors where slam-locking is not required.

FUNCTION: Key activated locking and unlocking. Deadlocks in both locked and unlocked position.

TECHNICAL DATA

STANDARD FINISH: Galvanized **COVER:** Cold-rolled steel plate

CASE: Malleable iron

LOCK BOLT: Cold-rolled steel with 1/4" diameter

case-hardened steel insert pins

PARACENTRIC CYLINDER & KEYS: Silicon

bronze/copper alloy

TUMBLERS: .097" spring temper brass.
Tumblers actuated by phosphor bronze springs,

5 tumblers per lock.



